


REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A3	-	RELEASE NEW DWG FORMAT	26DEC13	JARRY			



NOTES: UNLESS OTHERWISE SPECIFIED


1 MATERIAL


HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER

- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 13 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
 - 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.
 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: AT06-3S* RECEPTACLE (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.





CONTACT	MIN. INSUL	MAX. INSUL	TYPICAL	
SIZE	O.D.	O.D.	WIRE RANGE	
16	2.24 mm (.088 in)	3.68 mm (.145 in)	14 - 20 AWG	





PART NUMBER CHART				
COLOR	PART NUMBER			
GREY	AT04-3P			
BLACK	AT04-3P-BLK			
BLUE	AT04-3P-BLU			
BROWN	AT04-3P-BRN			
GREEN	AT04-3P-GRN			
RED	AT04-3P-RED			
WHITE	AT04-3P-WHT			
YELLOW	AT04-3P-YEL			





	SEE PART N	UMBER CHART	7				
	PART N	RT NUMBER		DESCRIPTION		ITEM -	
QUANTITY		MA	TERIALS LIST				
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm). 2) Tolerances are as follows: 1 PL DEC +0.30. I Fractions +1/64		SIGNATURE	S DATE	= Amnnendi			
		DRAWN: JARRY	26DEC13				
1 PL DEC ±0.30 Fractions ±1/64 2 PL DEC ±0.15 Angles ±1° 3 PL DEC ±0.08		CHECKED:		Sine Systems - www.amphenol-sine.com		_	
3) Note reference = X ENGIN		ENGINEER:	44724 Morley Drive Clinton Township, MI 48036				
MATERIAL SPECIFICATIONS: APPROVAL:				Olliton Township, Wil 40	000		
		CUSTOMER:		RECEPTACLE, 3 PIN, AT SERIES			s
THIS DRAWING IS SUPPLI							
PROCESS SPECIFICATIONS:		SPECIFICATIONS AND PERFORMANCE DATA SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION. NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO NORMAL		B C-	AT04-3F	P-XXX	A3
NEXT ASS'Y:				SCALE NONE		SHEET 1 OF	1