




REVISIONS							
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A3	-	RELEASE NEW DWG FORMAT	18/OCT/13	DRP	-		





AMPHENOL ATP06-28

18.6



NOTES: UNLESS OTHERWISE SPECIFIED

- MATERIAL:
 HOUSING: THERMOPLASTIC
 SEAL: SILICONE RUBBER
- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:

12

- 3.1 CURRENT RATING: 25 AMPS
- 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
- 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC.
- 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

(.195 in)

10 - 14 AWG

- 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
- 3.6 MATING CYCLE DURABILITY: 100 CYCLES
- 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP04-2P* RECEPTACLE. (* = MODIFICATIONS AND COLORS)

(.134 in)

5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.



PART N	PART NUMBER CHART					
COLOR	PART NUMBER					
GREY	ATP06-2S					
BLACK	ATP06-2S-BLK					

STANDARD MOLDED COLOR IS GREY. ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

	SEE PART NUMBER CHART								
	PART NUMBER			DESCRIPTION			ITEM		
QUANTITY		RT NUMBER DESCRIPTION ITEM - MATERIALS LIST IFFED DRAWN D.PARKS 180CT/13 Amphenol 11/64							
			RES DATE			Λ	mnho	no	I
All dimensions are in metric(mm). Tolerances are as follows: PL DEC ±0.30 Fractions ±1/64		I D.PAKNO I		18/OCT/1/3 Ampliend					I
2 PL DEC ±0.15 3 PL DEC ±0.08	Angles ±1°	CHECKED:			Sine Systems - www.amphenol-sine.com				
3) Note reference = X MATERIAL SPECIFICATIONS: PROCESS SPECIFICATIONS:		ENGINEER:							
		APPROVAL:			Clinton Township, MI 48036				
		CUSTOMER:		PLUG. 2 SOCKET, ATP SERIES					
		THIS DRAWING IS SUPPLIED FOR INFORMATION ONLY: DESIGN FEATURES,							
PROCESS SPECIFICA	HUNS.	SHOWN HEREON ARE THE THE AMPHENOL CORPOR OF REPRODUCTION ARE	RAMING IS SUPPLIED FOR MAINTON ONLY DESIGN FEATURES, MICHOROUS AND PERFORMANCE DATA HERCAL ARE PROPERTY OF A SIZE TYPE DWG NO: REVISION NERCOLARS THE PROPERTY ON RIGHTS B C - ATPO6-2S-XXXX A3						
NEXT ASS'Y:		MANUFACTURING VARIATIONS.		SCALE: N	ONE		SHEET 1	or 1	

REFER TO PART NUMBER CHART FOR

AVAILABLE CONNECTOR COLORS