




	REVISIONS						
REV	ECO	DESCRIPTION	DATE	BY	APPR		
A3	-	RELEASE NEW DWG FORMAT	18/OCT/13	DRP	-		







REFER TO PART NUMBER CHART FOR


AVAILABLE CONNECTOR COLORS

NOTES: UNLESS OTHERWISE SPECIFIED

- 1 MATERIAL HOUSING: THERMOPLASTIC SEAL: SILICONE RUBBER
- 2. MODIFICATIONS: N/A
- 3. SPECIFICATIONS:
 - 3.1 CURRENT RATING: 25 AMPS
 - 3.2 OPERATING TEMPERATURE: -55°C TO +125°C
 - 3.3 DIELECTRIC WITHSTANDING VOLTAGE: LESS THAN 2 MILLIAMPS CURRENT LEAKAGE @ 1500 VOLTS AC. 3.4 INSULATION RESISTANCE: 1000 MEGOHMS MIN @ 25°C.

 - 3.5 MOISTURE RESISTANCE: IP67 (MATED CONDITION)
 - 3.6 MATING CYCLE DURABILITY: 100 CYCLES
 - 3.7 RoHS COMPLIANT
- 4. MATING PART: ATP06-4S* PLUG. (* = MODIFICATIONS AND COLORS)
- 5. ALL DIMENSIONS ARE FOR REFERENCE USE ONLY.

/6\	CONTACT	SIZE AND REA	AR SEAL WIRE	: RANGE:
	CONTACT SIZE	MIN. INSUL O.D.	MAX. INSUL O.D.	TYPICAL WIRE RANGE
	12	3.40 mm (.134 in)	4.95 mm (.195 in)	10 - 14 AWG



PART NUMBER CHART			
COLOR	PART NUMBER		
GREY	ATP04-4P		
BLACK	ATP04-4P-BLK		

STANDARD MOLDED COLOR IS GREY, ADDITIONAL COLOR (BLACK) IS AVAILABLE VIA SPECIAL ORDER.

UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm)	
QUANTITY	

QUANTITY MATERIALS LIST						
UNLESS OTHERWISE SPECIFIED 1) All dimensions are in metric(mm).	SIGNATURES	DATE	Amphenol			
Tolerances are as follows: 1 PL DEC ±0.30 Fractions ±1/64	D.PARKS	18/OCT/13	Amphenoi			
2 PL DEC ±0.15 Angles ±1° Angles ±1°	CHECKED:		Sine Systems - www.amphenol-sine.com			
3) Note reference = X	ENGINEER:		44724 Morley Drive			
	APPROVAL:			Clinton Township, MI 480	J36	
MATERIAL SPECIFICATIONS:	SHOWN HEREON ARE THE PROPERTY OF THE AMPHENOL CORPORATION, NO RIGHTS OF REPRODUCTION ARE IMPLIED. ALL DIMENSIONS ARE SUBJECT TO MORMAN		RECEPTACLE, 4 PIN, ATP SERIES			
PROCESS SPECIFICATIONS:						
			B C-	ATP04-4P		A3
NEXT ASS'Y:			SCALE NONE		SHEET 1 OF	1